



Go eco with the
environmentally friendly
CSBR® range

Colour Options

* Included colours are batch specific and may vary from this image
Colour samples are indicative only. Please refer to actual samples for accurate colour guides.



rose



red



terracotta



sand yellow



mid green



dark green



orchid



purple



dark blue



mid blue



aqua



emerald



jazz*



grey



eggshell



beige



auburn



cocoa

About CSBR®

CSBR® (coloured styrene-butadiene rubber) is made of granulated tyre rubber coated with quality resins and pigments to achieve a thorough and even coloured coating.

- Largest colour range - 18 colours to choose from.
- Highest durability - Specially developed coating.
- Best U.V. resistance - Quality pigments and resins.
- Consistent colours - Produced in 900m² batches.
- Produced from recycled Australian tyres - Independently green certified.
- Great surface elasticity - Nothing compares to the quality of tyre rubber.
- Easy to lay - Better and tighter surface finishes.





DATA SHEET

Effective October 01, 2018

Product Overview

Used extensively in Australia for wetpouring various surfacing applications, A1 Rubber's™ CSBR® pre-coloured rubber has cleaned up the job environment of trowelling down rubber. No longer do applicators go home covered in oxide. CSBR® virtually eliminates those unsightly colour variations between batches.

CSBR® is available in 18 colours and is made in batches of 9 tonnes so jobs up to 900m² can be laid from the one batch.

Specifications

Particle Sizes	1-4mm	Density	Loose Granules - Approx 500kg/m ³ Troweled Granules - Approx 700kg/m ³
Coating Type	Milled pigments in baked on polyurethane	Pack Size	20kg perforated, UV treated plastic valve sacks
Approx Coverage	Granules - 1.7m ² @ 15mm / 2.4m ² @10mm on flat sub-base	Sieve Analysis	<2.0mm - 15% <4.0mm - 85%
Colour Fastness	See UV resistance document.		

Applications

Used extensively in Australia for wetpouring various surfacing applications such as, playgrounds, walkways, outdoor areas and non-slip surfaces.

Colours



*Included colours are batch specific and may vary from this image.

Disclaimer

The above information is derived from periodic tests taken on actual product from the manufacturing process. Some variances in specifications and raw surface appearances are possible due to the use of recycled materials and our manufacturing tolerances. In practice, the difference in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The recommendation relating to the application and end use of A1 Rubbers™ products, are given in good faith, based on A1 Rubbers™ current knowledge and experience of the product when properly stored, handled and applied under normal conditions in accordance with A1 Rubbers™ recommendations. The user of the product must test the product's suitability for intended application and purpose. A1 Rubber™ reserves the right to change the properties and tolerances of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current Terms and Conditions of Sales and delivery. Users must refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Document No. CSBROCT18DATA