



20mm SHOCK PAD UNDERLAY TILES

Shock pad underlay provides an additional protective and impact-absorbing layer installed directly underneath synthetic grass surfaces. Constructed from closed cell foam, Aloro Shock Pad underlay provides fall protection, facilitates drainage and is specially developed to stand up to rigorous use in sporting field applications.

Our 20mm shockpad tiles feature an easy interlocking tile system and are constructed from high density and eco-friendly foam excess that is prevented from entering landfill. With each individual tile having a coverage of approx. 1m², it's easy to calculate your requirements and minimise waste.

Please note: The colour of this product varies due to its recycled nature.

20mm SHOCKPAD TILES		
CODE	RSP-90020-SHOCKPADTILE	
FORMAT	Interlocking Tiles (per m ²)	
TILE SIZE	1120 x 900mm (1.008m ²)	
THICKNESS	20mm (±10%)	
MATERIAL	XLPE	
DRAINAGE	Vertical and Horizontal, >3000 mm/h	
DENSITY	100kg /m ³	
SHOCK	ABSORPTION	57.4%
VERTICAL	DEFORMATION	9.5mm
TENSILE	STRENGTH	4.21 kN/m
CRITICAL FALL HEIGHT	0.98m*	



*Actual test onsite is required to certify the CFH